


Basis Z

EDOF

Single piece, sterile, foldable aspheric hydrophobic acrylic intraocular lens (IOL) with UV blocker and blue light filter. The optic is EDOF, with refraction-based central Wavefront Linking zones. The IOL is available as part of a preloaded injector system.



MATERIAL

Hydrophobic acrylic with UV blocker and blue light filter

Refractive Index

1,47

Abbe Number

58

DESIGN

Optic Diameter
Overall Diameter

6 mm

13 mm

Optic Design

Aspheric - Aberration Neutral
Biconvex (+8.0 D → +30.0 D)

Nominal A-constant

118,9

Haptic Design

Posterior vaulting Z-haptic with 0° angulation

PCO Prevention

360° sharp edge

Shelf Life

2.5 years after sterilization

INJECTION

Estimated Incision Size

2.2 mm

Compatible Injector

POB-MA SINGLE-USE
PRELOADED INJECTOR

CONSTANTS

for optical and immersion ultrasound measurements

SRK/T A-Constant

A = 118.824*

Haigis

a0 = 0.3136
a1 = 0.1158
a2 = 0.1758

Hoffer Q

pACD = 5.411

Holladay I

SF = 1.662

Barrett Universal II

LF = 1.79


Holladay II

ACD = 5.444

*Based on IOL Con 03.2023

Basis Z

EDOF



POWER RANGE

Article No. Yellow	SEQ/Powers	Steps	Cylinders	Steps	Addition
B1XBY0	+8.0 D to +30.0 D	0,5 D			
S1XBY0	+31.0 D to +35.0 D	1.0 D			



1stQ GmbH

Konrad-Zuse-Ring 23 | 68163 Mannheim
Germany



Leading
IOL solutions

www.1stq.eu
www.1stq.de/en